

## VITANOVA

Special water-based acrylic product protects the hardwood floor with Invisible Touch finish. Its periodical application helps to keep the homogeneity and to increase the surface protection.

### DIRECTION FOR USE

If the surface of the floor shows evident signs of wear and tear, especially in higher traffic areas, and washing with Green Bio Listone Giordano® is no longer sufficient to restore its appearance, we recommend the use of Vitanova Listone Giordano®.

Before applying it, thoroughly clean the surface of the floor using Green Bio Listone Giordano® in double dose according to the instructions in the PM 29 technical sheet.

Always use Vitanova Listone Giordano® at temperatures above +15°C.

If the air temperature is above 25°C approx. or there is a strong ventilation or an exposure to direct sunlight, the product may have a reduced drying time and require greater care in spreading.

After washing wait until the floor is completely dry.

**Shake well before each use (until all residuals are dissolved).**

Spread homogeneously a thin layer of Vitanova Listone Giordano® pure as if to clean in the direction of the plank's length, using Listone Giordano® microfiber cloth (or alternatively a soft lint free cotton cloth that will not leave fibre residues) underneath a long-handled floor brush or by hand in case of a small surface.

We recommend applying a limited quantity of Vitanova Listone Giordano® because it could permeate the brushings making it difficult to remove.

Once the product is applied, the floor's surface should have a slightly wet appearance.

After 1-2 hours, the floor is dry and you can walk upon it.

Do not wash the floor for at least 2 days.

The application of Vitanova Listone Giordano®, as above described, helps to homogenize the floor; no polish or other application is therefore required.

Use this product approximately every 6-8 months in the first year after the installation of the hardwood flooring and every 6-12 months from the second year on.

Anyway Vitanova Listone Giordano® has to be applied whenever the flooring appears dry or shows signs of wear and tear from everyday use or it retains dust and dirt or has a lower resistance to liquids.

We recommend more frequent maintenance operations in case of average and heavy-duty traffic environments.

1 litre of product is sufficient for spreading a coat on a surface area of approximately 25-30 m<sup>2</sup>.

Keep the product closed in its original package, in a cool place, away from freeze and UV rays.

Never use liquids containing acid or basic concentrations, such as bleach or ammonia, which could create marks/halos on the wood that would be impossible to remove.

Never wash the floor with water only: it will not efficiently clean the surface of the floor and the minerals contained in water may leave behind a residue that could affect the surface appearance of the floor.

PM 40 – October 2021

While this product is not classified as dangerous or flammable, keep out of the reach of children.

The information contained on this sheet are based on the company's research and experience.

However it is intended for general purposes only since it is impossible to predict every environmental and installation variable.